

strapex

SMG 65

**High performance machine
for plastic strapping**

NEW



For large and heavy packages

SMG 65

Cost effective, efficient Easy operation

Highlights

Easy operation	Touch Panel Easy fault clearance without tools
High availability	Secure strap guide thanks to exclusive closed strap guide system
Flexibel	For integration into conveyor systems or as stand alone machine with non-driven rollers



Strap tension easily adjustable with press button



Simple coil change



Easily accessible, maintenance without tools

Strapex advantage



Machine, strap and after-sales service as a total package



Options
Adaptable to different operating conditions and requirements



Strap for cost effective strapping
Use of thin PP strap

Technical data

Cycles per minute, up to	65
Arch dimension (width x height)	650 x 500 mm
	850 x 850 mm
	850 x 1250 mm
	850 x 1550 mm
Seal height	560–1040 mm
Electrical supply	230 V, 50 Hz
	115 V, 60 Hz
Strap tension	
– with manual feed, up to	450 N
– with automatic feed (Option), up to	600 N
Emission sound pressure level	79 dB (A)
Weight	190 kg

Plastic strap: Polypropylene (PP)	
9 mm	371.609.555
12 mm	371.612.540
Strap coil, inside/outside Ø	200/430 mm

Packages	
Min. width x height	50 x 100 mm
Package weight, max.	50 kg

U.K.
Strapex
Unit 50
Empire Industrial Park
Empire Close
Aldridge, Walsall, WS9 8UQ
Phone +44 1922 742 500
Fax +44 1922 742 501

USA
Acme
An ITW Company
501 W. Lake Street, Suite 105
Elmhurst, IL 60126
Phone 630-589-5100
Fax 630-589-5101

Australia
IWD Strapping Sales Pty Ltd.
P.O. Box 215
Melbourne Vic 3001
Phone 1 800 779 380
Fax 1 800 779 583

India
Strapex India Limited
506, Center Point, J.B. Nagar
Andheri-Kurla Road, Andheri (E)
Mumbai - 400 059
Phone +91-22-66400204/05
Fax +91-22-28252932

www.strapex.com